

| MODEL | BEAM (MM) | REC. HP (SINGLE / TWIN) | MAX HP | # PAX | DRY / WORK WEIGHT (KG) | ENGINE SHAFT (IN.) | CHAMBERS | IN-BUILT FUEL (L) | DEADRISE (DEGREES) |
|-----------------------------------|----------------------|--|-------------------|------------------|-----------------------------------|-------------------------------|-----------------|------------------------------|-------------------------------|
| 3.1M SEARAIDER | 1450 | 8 | 10 | 3 | 90 / 400 | 15 | 3 | EXTERNAL | 12 |
| 3.4M SEARAIDER | 1600 | 15 | 15 | 3 | 95 / 400 | 15 | 3 | EXTERNAL | 12 |
| 3.8M SEARAIDER | 1820 | 25 | 30 | 3 | 155 / 500 | 15 / 20 | 4 | EXTERNAL | 12 |
| 4.2M SEARAIDER | 1820 | 30 | 40 | 4 | 170 / 600 | 15 / 20 | 5 | EXTERNAL | 12 |
| 4.5M SEARAIDER | 2080 | 2X30 / 1X70 | 70 | 5 | 190 / 800 | 20 | 5 | EXTERNAL | 12 |
| 4.8M SEARAIDER | 2090 | 2X30 / 1X85 | 85 | 6 | 220 / 900 | 20 | 5 | EXTERNAL | 12 |
| 5.2M SEARAIDER | 2300 | 2X50 / 1X100 | 115 | 8 | 320 / 990 | 20 / 25 | 6 | 130 | 26 |
| 5.6M SEARAIDER | 2400 | 2X60 / 1X115 | 140 | 8 | 366 / 1000 | 20 / 25 | 6 | 130 | 26 |
| 5.9M SEARAIDER | 2400 | 2X60 / 1X130 | 150 | 8 | 390 / 1000 | 20 / 25 | 6 | 130 | 26 |
| 6.2M SEARAIDER (N) | 2400 | 2X70 / 1X150 | 180 | 11 | 488 / 1070 | 20 / 25 | 6 | 200 | 26 |
| 6.2M SEARAIDER (W) | 2670 | 2X70 / 1X150 | 180 | 11 | 500 / 1070 | 20 / 25 | 6 | 200 | 26 |
| 6.5M SEARAIDER (W) | 2670 | 2X70 / 1X150 | 200 | 12 | 550 / 1120 | 20 / 25 / 30 | 6 | 200 | 26 |
| 6.6M SEARAIDER | 2450 | 2X70 / 1X150 | 200 | 12 | 520 / 1200 | 25 / 30 | 6 | 200 | 26 |
| 7.5M SEARAIDER | 2820 | 2X115 | 300 | 15 | 850 / 1350 | 25 / 30 | 10 | 200 | 24 |
| 8.5M SEARAIDER | 2820 | 2X150 | 400 | 17 | 920 / 1600 | 25 / 30 | 10 | 200 | 24 |
| 9.5M SEARAIDER | 2820 | 2X175 | 450 | 18 | 1350 / 1800 | 25 / 30 | 12 | 2 X 200 | 24 |